# 1PH / 2-LINE + GROUND HEMP FILTER

## SPECIFICATIONS

MAX VOLTAGE: 0-277/0-480VAC
RATED CURRENT: 100A/LINE
OPERATING TEMP.: -40 TO 65C
HIPOT (L-G): 2200VDC
TERMINALS: M10
DISCHARGE VOLTAGE (@277V)
<20V IN 1 MINUTE
VOLTAGE DROP: <2% MAX AT FULL
RATED UNITY LOAD
PERFORMANCE: Mil-STD-188-125-1A
TYP. WEIGHT, LBS (KG): 110 (50)
GND STUD: M10 (EACH ACCESS AREA)
MANUFACTURED FOR WALL MOUNTING
FOR INDOOR CONTROLLED ENVIRONMENTS.
ALL EMI SEAMS 100% WELDED AND OUTPUT
ACCESS SEALED WITH EMI GASKET.




Conforms to UL STD 1283

5026929
Conforms to UL STD 1283

**Made in the USA**

| LV1A-H-2L-100A-480V | |
|---|---|
| TSS USA, LLC | REV: |
| CAGE CODE | PROPRIETARY NOTE: NOTICE TO ALL PERSONS RECEIVING THIS DRAWING. THIS DOCUMENT IS THE PROPERTY OF TSSUSA AND IS NOT TO BE DISCLOSED, REPRODUCED IN WHOLE OR IN PART OR USED FOR MANUFACTURING PURPOSES BY ANYONE WITHOUT THE CONSENT OF TSS AND PREMIER. |
| 56NX9 | |